

Technical Data Sheet

updated
checked

03.01.2020
03.01.2020

Product	WhiteBack PES-Gewirke, beschichtet und INKTeX+® FL Ausrüstung 7255KMFLW with additional, onesided PU-block-out coating, white
Material	100 % Polyester
Stock widths	app. 320 cm
Making-up	rolled on paper cores
Packaging	wrapped with foil
Ink-type	direct printing with UV curing inks, direct printing with HP Latex inks
characteristics	Flame retardant, air tight, elastic, blockout, water repellent

Weight acc. to DIN EN 12127	335.00	[g/m ²]	+ - 5	[%]
--------------------------------	--------	---------------------	-------	-----

Tearing strength

Elongation at 100 N, longitudinal direction acc. to DIN EN ISO 13934-1	18.00	[%]	+ - 20	[%]
---	-------	-----	--------	-----

Elongation at 100 N, cross direction acc. to DIN EN ISO 13934-1	23.00	[%]	+ - 20	[%]
--	-------	-----	--------	-----

Maximum tensile elongation, longitudinal direction acc. to DIN EN ISO 13934-1	50.00	[%]	+ - 20	[%]
--	-------	-----	--------	-----

Maximum tensile elongation, cross direction acc. to DIN EN ISO 13934-1	75.00	[%]	+ - 20	[%]
---	-------	-----	--------	-----

We do not accept liability for errors. The confirmed properties are valid in the state of delivery. Any further processing can change them (e.g. washing / flame retardancy). Please pay attention to our general considerations regarding fabrication at www.g-o-friedrich.com Printing mistakes and changes are reserved.